



Code	ECBGAS-M-LOG
Heat Output	2–5.2 kW
Fuel Type	Natural Gas
Width	465mm
Height	582mm
Depth	386mm
Nett efficiency	82.79%

Features

- Conventional Flue
- Lifetime guarantee
- Battery powered ignition - no need for mains electricity
- Easy to use remote control included as standard
- Adjustable heat output and flame height
- Top flue outlet
- Clear view glass screen

Ecoburn Plus Medium Gas - Technical information

Code	ECBGAS-M-LOG
Gas type	Natural Gas (G20)
Nominal Heat Input - Minimum Rate (Gross)	2.5 kW
Nominal Heat Input - Maximum Rate (Gross)	6.2 kW
Gas consumption - Minimum Rate	0.230 m ³ /h
Gas consumption - Maximum Rate	0.578 m ³ /h
Gas connection	8 mm compression
Supply pressure (measured at test elbow)	20 mbar
Injector (x1)	Stereomatic 500
Oxypilot type	Erta PG-82 -10
Remote gas valve	TESC01 RF868-15
Flue diameter	125mm
Suitable for non-combustible 12mm hearth	Yes
Countries of Destination	GB and IE
Weight (unpacked)	41kg

Minimum Distance To Combustibles

To rear of stove	300 mm
To sides of stove	300 mm
Above stove	300 mm

Efficiency and Emissions

Nett Efficiency	82.79 %
Efficiency Class	1
NOx	2

